

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
20 October 2005 (20.10.2005)

PCT

(10) International Publication Number
WO 2005/097402 A1

(51) International Patent Classification⁷: B23Q 1/01, 1/62

(74) Agent: PIOVESANA, Paolo; Via F. Baracca, 5/A,
I-30173 Venezia Mestre (IT).

(21) International Application Number:

PCT/EP2004/003728

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 7 April 2004 (07.04.2004)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (*for all designated States except US*): HPT SINGER S.R.L. [IT/IT]; Piazza Salvemini, 7, 35100 Padova (IT).


(72) Inventors; and

(75) Inventors/Applicants (*for US only*): GUELLI, Francesco [IT/IT]; Via A. Vivaldi, 1, 35012 Camposampiero (IT).
PICCOLO, Gabriele [IT/IT]; Via A. Vivaldi, 1, I-35012 Camposampiero (IT).

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,

[Continued on next page]

(54) Title: HORIZONTAL MILLING-BORING MACHINE WITH MOBILE COLUMN



(57) Abstract: A horizontal milling-boring machine comprising a horizontal bed (6) anchored to the floor (8), a column structure (4) supported by the bed and slidable therealong, a slide carriage (22) slidable vertically along said column structure (4), and a slide (2) supporting the tool head (34) and movable axially to said carriage (22) in a direction perpendicular to the axis of said bed (6), characterised in that: - said bed (6) is monolithic and is separated from the work table (10), - said column structure (4) is formed as a portal, with two columns (16) connected together by an upper crosspiece (18) and provided lowerly, for their support on the bed, with portions (19) lying external to the opening of said portal, which is delimited laterally by said columns (16) and extends lowerly into proximity with said bed (6), - said slide carriage (22) is slidable along the facing internal walls of said columns (16), - guide means (26) and drive means (28, 30, 32) being interposed between said column structure (4) and said bed (6).

WO 2005/097402 A1



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*